PPF AFTERCARE & MAINTENANCE

Recommended care after installation

PROTECT THE FILM. PRESERVE THE FINISH.
Proper care during the first days after installation helps the film and adhesive system settle correctly and supports long-term appearance and performance.

FIRST 48 HOURS

Avoid driving above 80 km/h (50 mph) whenever reasonably possible. Do not press, peel, puncture or manipulate film edges.

DAYS 3-5

Do not wash the vehicle during the first 3-5 days after installation. Allow the film and adhesive to settle.

DAY 7-10

Schedule the first professional inspection and maintenance check with your installer.

LONG-TERM CARE

- Avoid high-pressure washing. Never direct high-pressure water closely at film edges, seams, corners or lifted areas.
- Use a gentle automotive wash method with clean, soft wash media and suitable automotive cleaning products.
- Do not use harsh chemicals, strong solvents, abrasive cleaners or aggressive compounds on the film.
- Do not use sharp objects, scrapers, hard brushes or abrasive surfaces on the film.
- Do not use clay bars, clay mitts or other clay-based products on the PPF surface.
- Never intentionally peel, pull, lift or manipulate PPF edges or seams.

REMOVE CONTAMINANTS QUICKLY

Bird droppings, insects, tree sap, fuel residue and environmental contamination should be removed as soon as possible. Soften and clean gently - do not scrape or aggressively rub the film.

MAINTENANCE SCHEDULE

- First professional inspection: 7-10 days after installation.
- Ongoing inspection and maintenance: every 6 months during the warranty period.

IMPORTANT

Do not attempt to repair or remove the film yourself. Failure to follow Grizzly Protection's aftercare and maintenance instructions may affect warranty coverage where improper care contributed to the damage or Product failure.

Protect the film. Maintain the finish. Preserve the performance.